

U.S. DIVISIONAL PATENT APPLICATION

**TACKED COILED FOOD PRODUCTS AND METHOD OF FABRICATING**

DAVID E. BABIARZ  
RONALD T. CAPPADOCIA  
WILLIAM E. LUNDGREN, JR.

Attorney Docket No. 91885/501

Steven J. Goldstein  
Registration No. 28,079  
FROST BROWN TODD LLC  
2200 PNC Center  
201 East Fifth Street  
Cincinnati, Ohio 45202  
(513) 651-6131

"Express Mail"

Mailing Number: EK652697314US

Date of Deposit: March 9, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office in Addressee" service under 37 CFR 1.10 and is addressed to The Commissioner of Patents and Trademarks, Washington, D.C. 20231.

KELLY A. KUHL

Print Name

  
Signature

## TACKED COILED FOOD PRODUCTS AND METHODS OF FABRICATING

### DESCRIPTION

#### Related Applications

This Application claims the benefit of U.S. Provisional Patent Application Serial Number 60/158,456, filed October 8, 1999.

#### Technical Field

5           The present invention generally relates to food items and methods of fabricating, and in particular to the packaging of a food material strip in a manner appealing to consumers.

#### Background of the Invention

10           The merchandising of snack-type food products is a highly competitive business. In addition to the particular type of food material within these products, the novelty and play value are also important factors to consumers when deciding whether to purchase the product.

15           For example, a snack product such as FRUIT ROLL-UPS has found wide market acceptance. This product comprises a dehydrated fruit-based strip of material that must be unrolled and peeled from the packaging. Although dehydrated fruit-based snacks are not new, the process of unrolling and peeling a strip of candy from its packaging is appealing to children and some adults.

#### Summary of the Invention

20           The present invention is a food item and a method of fabricating wherein the food item is packaged in a manner promoting marketability. The food item includes a food material strip or belt having a predetermined length defined by a leading end and a trailing end. The strip is rolled around its leading end into a roll having multiple rotations with an outermost layer in contact with an inner layer. Furthermore, a region of the outermost layer proximate to the trailing end is tacked to the inner layer.

25           The food item can be manufactured by using a fork to coil the strip of food. Then, the outermost layer of the coil proximate to the trailing end of the strip can be tacked to an inner layer of the coiled strip.

### Brief Description of the Drawings

In the accompanying drawings forming part of the specification, and in which like numerals are employed to designate like parts throughout the same,

FIGURE 1 is a perspective view of a food item in accordance with the present invention that has been removed from a bag and includes a tacked coiled strip of food material coated with sugar granules;

FIGURE 2 is a side view of the coiled food item of FIGURE 1;

FIGURE 3 is a top view of an embodiment of a tacking device along with the coiled food item of FIGURE 1 prior to tacking;

FIGURE 4 is a cross sectional view of the food item shown in FIGURE 3 taken along plane 4-4;

FIGURE 5 is similar to FIGURE 4, but with the tacking device injected into the coiled food item;

FIGURE 6 is similar to FIGURE 5, but with the tacking device withdrawn from the coiled food item;

FIGURE 7 is a table listing the preferred ingredients of the food material of FIGURE 1;

FIGURE 8 is a schematic view of a fabrication system having a plurality of mechanisms for coiling and tacking strips of food material in accordance with the present invention;

FIGURE 9 is an elevated view of one of the coiling and tacking mechanisms of FIGURE 8, before receiving a strip of food material, and having a fork, a tacking device and a sensor device;

FIGURE 10 is a perspective view of the tacking device associated with the coiling and tacking mechanism of FIGURE 9;

FIGURE 11 is a perspective view of the coiling and tacking mechanism of FIGURE 9;

FIGURE 12 is an elevated view of the mechanism of FIGURE 9 receiving a strip of food material;

FIGURE 13 is an elevated view of the mechanism of FIGURE 12 after coiling the strip of food material;

5        FIGURE 14 is an elevated view of the mechanism of FIGURE 13, but with the prongs of the tacking device injected into the coiled strip of food material;

FIGURE 15 is a perspective view of the mechanism of FIGURE 14, but with the tacked coiled strip of food released from the mechanism; and,

10        FIGURE 16 is a partial plan view of the mechanism of FIGURE 15 depicting the fork in the retracted, second position, to release the tacked coiled strip of food.

#### Detailed Description

15        While this invention is susceptible of embodiments in many different forms, there is shown in the drawings and will herein be described in detail a preferred embodiment of the invention with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and is not intended to limit the broad aspect of the invention to the embodiments illustrated.

20        Referring to FIGURES 1-2, a food item 10 in accordance with the present invention is depicted comprising a tacked coiled belt or strip 12 of food material 14 sanded or coated with sugar granules. The food strip 12 consists of candy or a like food substance such as a sour flavored food material comprising the ingredients shown in FIGURE 7.

25        The food strip has two planar side surfaces 18, 20, a leading end 22, an opposite trailing end 24, and two parallel edges 26, 28 extending longitudinally. The length of the food strip 12 extends from the strip's leading end 22 to its trailing end 24. The width of the food strip 12 extends between the strip's parallel edges 26 and 28.

The strip of food material 12 is sanded or coated on both side surfaces 18, 20 with sugar or the like. The strip 12 is coiled multiple times around the leading end 22 to define a plurality of loops or layers in overlapping relationship. Each loop or layer

has a side surface in contact with, and thus supported by, another side surface of the strip of food material 12.

In an embodiment, an end portion or region 36 of the strip 12 proximate to the trailing end 24 is attached by tacking to an inner layer of the strip to prevent uncoiling of the food item. Moreover, the coiled food item 10 can be enclosed within a sealed plastic bag 38 or the like to preserve the freshness of the food material.

Turning to FIGURES 3-6, an embodiment of a method for fabricating a food item 10 in accordance with the present invention is depicted. As shown in FIGURES 3 and 4, prior to tacking the coiled strip 12 of food material 14, a tacking device 40 is provided having, in an embodiment, a heating element 42 and a pair of prongs or needles 44 and 46. The heating element 42 heats the needles 44, 46 to a predetermined temperature of, preferably, about 160 degrees Fahrenheit. The needles 44, 46 are injected into the coiled strip 12 such that the needles 44, 46 penetrate the outermost layer 48 of the coil and also penetrate into an inner layer 50 adjoining the outermost layer as shown in FIGURE 5.

The heating of the food material 14 about the needles 44, 46 tacks the associated portion 38 of the outermost layer 48 to the inner adjoining layer 50 of the coiled strip 12. Then, the needles 44, 46 are removed as shown in FIGURE 6 and the coiled strip 12 can, if desired, be deposited into a bag 38 or the like.

In an alternative embodiment, the needles 44, 46 can be injected through multiple layers of the coiled strip 12. Further, only one needle can be used for tacking the coiled strip 12, or if desired, more than two needles.

Turning back to FIGURES 1-2, in another embodiment, the region 36 of the strip 12 proximate to the trailing end 24 is tacked or welded to the inner layer 50 of the strip 12 by pressing portions of the outermost layer 48 against portions of the inner layer. In this alternative embodiment, no heat is used to tack the layers together.

FIGURE 8 provides a schematic view of a fabrication system 52 having a plurality of mechanisms 80 for coiling and then tacking strips of food material by

pressing portions of two layers together. The system 52 includes an extrusion head 56 for forming a plurality of spaced, parallel, narrow strips 12 of food material 14. The extrusion head 52 receives food material that is heated to an amorphous state allowing for even extrusion of the strips 12 of food material onto an endless conveyor belt 58.

5 The strips 12 of food material 14 are directed through a bath 60 of edible oil 62 and onto another endless conveyor belt 64 extending through a cooling tunnel 66. The oil, such as CAPOL or the like, preferably consists of a curing agent to keep acid in the strips 12. The temperature of the food material 14 is lowered as it passes through the cooling tunnel 66 for converting the food material 14 from an amorphous state to a  
10 pliable solid.

The strips 12 of food material exiting the cooling tunnel 66 are next directed onto an endless stainless steel wire mesh conveyor belt 68. The conveyor belt 68 extends through a conventional device, known in the art as a sander 70, for evenly spreading and pressing granules of sugar onto the strips 12. This process, known in the art as sanding,  
15 attaches the sugar granules to the outer surface of the strips 12.

The strips 12 of food material exiting the sander 70 are passed onto an inclined endless conveyor belt 72 for transporting the strips onto an elevated conveyor system 74 consisting of a plurality of elevated conveyors 76 separated from each other by a plurality of divides 78. Mounted below the elevated conveyor system 74 are a  
20 plurality of mechanisms or stations 80 for individually coiling and tacking the strips 12 of food material as explained in detail further herein.

As shown in FIGURE 8, each strip 12 of food material is transferred from the elevated conveyor system 74 onto a respective inclined endless conveyor belt 82 wherein the strip is cut by a knife 84 to define the trailing or cut end 24 of the strip. The leading  
25 end 22 of each strip 12 is received between first and second spaced parallel legs or tines 86, 87 of a fork 88 associated with a corresponding coiling and tacking mechanism 80. The legs 86, 87 of each fork 88 preferably have a length at least equal to the transverse width of an individual strip 12 of food material 14.

Turning to FIGURES 9 and 11, the fork 88 of each coiling and tacking mechanism 80 is operably connected, via a shielded drive coupling 91, to a motor 90 for rotating the fork 88 about an axis located parallel to the legs 86, 87. Fork 88 is reciprocated between a first, engaged or extended position (FIGURES 9, 11-14) extending generally in line with the path of the strip 12 exiting the associated inclined conveyor belt 82 (FIGURE 8), and a second, disengaged or retracted position (FIGURES 15 and 16) located to one side of the inclined conveyor 82 and transversely spaced from the first, engaged position. Preferably, fork 88 is reciprocated from the first and second positions, and vice versa, by a double-action pneumatic cylinder 92.

Each coiling and tacking mechanism 80 includes a pressure application device 94 for maintaining pressure against the food strip 12 as the strip is being coiled. Accordingly, the strip 12 is prevented from uncoiling by the pressure application device 94 before, and while, the coiled strip is being tacked. The pressure application device 94 preferably consists of a metal or metal alloy beam 96 having an arcuate end 98 and a bias member attachment end 100. The pressure application device 94 is pivotally coupled to a fixed intermediate member 102 to allow the beam 96 to pivot about the fixed member 102. The attachment end 100 of the beam 96 is coupled to a spring-load 104 comprising a spring 106 mounted about a shaft 108 having a distal end cap 109 attached thereto and in abutting relationship to the spring.

The arcuate end 98 of the pressure application device 94 reciprocates between a first inner position (FIGURES 9 and 12), wherein the arcuate end 98 is radially spaced by a predetermined distance "d" from the fork 88 in its extended position, and a second outer position (FIGURES 13 and 14), wherein the arcuate end 98 is radially spaced from the fork in its extended position by a distance greater than "d."

The arcuate end 98 of the pressure application device 94 is pressed against the food strip 12 by the spring-load 104 during at least a portion of the coiling of the food strip. Accordingly, the arcuate end 98 of the pressure application device 94 is moved from the first inner position (FIGURE 9) to the second outer position (FIGURES 13 and

14) as the outer diameter of the coiled food strip 12 increases in outer diameter size during the coiling process. Correspondingly, once the coiled food item is removed from the fork 88, the arcuate end 98 of the pressure application device 94 moves from the second outer position to the first inner position by the force applied by the spring-load 104 to the bias attachment end 100 of the pressure application device.

Turning to FIGURE 12, in operation, the leading end 22 of a food strip 12 is fed by the inclined conveyor belt 82 (FIGURE 8) between the legs 86, 87 of the fork 88 while the fork is positioned in its first engaged position and being stationary with the legs located to allow the leading end 22 of the food item to be fed therebetween. Preferably, a sensor device 133 is provided for detecting when the leading end 22 of the food strip 22 has been fed between the legs 86,87 of the fork 88. In an embodiment, the sensor device 133 is a conventional laser sensor that emits a laser beam 137. When the strip 22 is fed between the fork legs 86,87, the laser beam 137 reflects off the strip and back to the sensor. The sensor detects the reflection and, as a result, provides for enabling the motor 90 to rotate the fork 88 about an axis parallel with the legs 86, 87.

With reference to FIGURE 12, the fork 88 is preferably rotated in a clockwise direction as shown by arrow "A." As the fork 88 is rotated, it can be appreciated that the strip 12 of food 14 is rolled into a coil around its leading end 22 on, and around, the legs 86, 87 of the fork as shown in FIGURE 13. In an embodiment, the motor 90 can rotate the fork 88 at adjustable speeds such that rotation of the fork is gradually decreased once the food strip 12 begins coiling about the fork. Likewise, if desired, the speed of conveyor belt 82 can be increased as the food strip coils about the fork 88.

Also, as the strip 12 of food 14 is rolled, the coil comes into contact against the pressure device's arcuate end 98 in its first, inner position. In its first inner position, the pressure device's arcuate end 98 places pressure on the rolling, coiled-up strip of food. Thus, the fork 88 acts as a rotating anvil, and with the pressure member's arcuate end 98, sandwiches the coiled-up strip of food therebetween.



Turning to FIGURE 14, after the fork 88 has rotated the desired amount of times to completely coil the strip 12 of food 14, rotation of the fork is slowed to a complete stop. At that time, a tacking device 140 having a pair of prongs 144 and 146 (FIGURE 10) maintained in spaced parallel relationship to each other are injected into the coiled strip 12. The prongs 144, 146 are connected to a double-action pneumatic cylinder 123 for injecting and, if desired, retracting the tips of the prongs 144, 146 from the coiled strip 12. Preferably, the prongs 144, 146 are a pair of spaced coplanar elongated strips fabricated of a metal or metal alloy with each prong having a tip 153 for injecting into the coiled food strip 12.

In an embodiment, the tips 153 of the prongs 144, 146 are injected into the outermost layer 48 of the coil to penetrate into the layer 50 adjoining the outermost layer. As the prongs 144, 146 are injected into the coil, a portion of the pressure application device's arcuate end 98 is positioned between the prongs while maintaining pressure against the coil to keep the coil from unraveling. Preferably, the terminal distal ends 173 of the prongs 144, 146 are blunted so that, by being injected into the coiled strip, the outer outermost layer 48 of the coil is pressed into, and thus becomes tacked to, the inner adjoining layer 50 of the coil.

After the coiled strip 12 has been tacked, the fork 88 is axially slid from the coiled food item 10 by reciprocating the fork transversely from its first, engaged position shown in FIGURES 9 and 11-14 to its second, disengaged position shown in FIGURES 15 and 16. The fork 88 is reciprocated by cylinder 92, with the individual tacked coiled strip of food 14 falling from the fork 88 as it is retracted. In an embodiment, the tacked coil of food falls onto a suitable collector means or removal conveyor, not shown.

As shown in FIGURE 16, the legs 86, 87 of the fork 88 are retracted through a corresponding pair of apertures 183 in a rotatable stationarily mounted disk 185, with the coiled strip of food abutting the disk and axially sliding from the fork as the fork is transversely reciprocated into the apertures. After the fork 88 has reciprocated to its second, disengaged position as shown in FIGURES 15 and 16, so the coiled strip 12 of

food 14 falls therefrom, the fork is moved back to its first, engaging position of FIGURE 12 by cylinder 92, wherein legs 86 and 87 are positioned to accept the leading end of the next strip 12 of food 14. Before the next strip of food is coiled, prongs 144, 146 are retracted away from fork 88 by double-action pneumatic cylinder 123.

5           While the specific embodiments have been illustrated and described, numerous modifications come to mind without significantly departing from the spirit of the invention and the scope of protection is only limited by the scope of the accompanying Claims.

FIG. 12  
FIG. 13  
FIG. 14  
FIG. 15  
FIG. 16  
FIG. 17  
FIG. 18  
FIG. 19  
FIG. 20  
FIG. 21  
FIG. 22  
FIG. 23  
FIG. 24  
FIG. 25  
FIG. 26  
FIG. 27  
FIG. 28  
FIG. 29  
FIG. 30  
FIG. 31  
FIG. 32  
FIG. 33  
FIG. 34  
FIG. 35  
FIG. 36  
FIG. 37  
FIG. 38  
FIG. 39  
FIG. 40  
FIG. 41  
FIG. 42  
FIG. 43  
FIG. 44  
FIG. 45  
FIG. 46  
FIG. 47  
FIG. 48  
FIG. 49  
FIG. 50  
FIG. 51  
FIG. 52  
FIG. 53  
FIG. 54  
FIG. 55  
FIG. 56  
FIG. 57  
FIG. 58  
FIG. 59  
FIG. 60  
FIG. 61  
FIG. 62  
FIG. 63  
FIG. 64  
FIG. 65  
FIG. 66  
FIG. 67  
FIG. 68  
FIG. 69  
FIG. 70  
FIG. 71  
FIG. 72  
FIG. 73  
FIG. 74  
FIG. 75  
FIG. 76  
FIG. 77  
FIG. 78  
FIG. 79  
FIG. 80  
FIG. 81  
FIG. 82  
FIG. 83  
FIG. 84  
FIG. 85  
FIG. 86  
FIG. 87  
FIG. 88  
FIG. 89  
FIG. 90  
FIG. 91  
FIG. 92  
FIG. 93  
FIG. 94  
FIG. 95  
FIG. 96  
FIG. 97  
FIG. 98  
FIG. 99  
FIG. 100  
FIG. 101  
FIG. 102  
FIG. 103  
FIG. 104  
FIG. 105  
FIG. 106  
FIG. 107  
FIG. 108  
FIG. 109  
FIG. 110  
FIG. 111  
FIG. 112  
FIG. 113  
FIG. 114  
FIG. 115  
FIG. 116  
FIG. 117  
FIG. 118  
FIG. 119  
FIG. 120  
FIG. 121  
FIG. 122  
FIG. 123  
FIG. 124  
FIG. 125  
FIG. 126  
FIG. 127  
FIG. 128  
FIG. 129  
FIG. 130  
FIG. 131  
FIG. 132  
FIG. 133  
FIG. 134  
FIG. 135  
FIG. 136  
FIG. 137  
FIG. 138  
FIG. 139  
FIG. 140  
FIG. 141  
FIG. 142  
FIG. 143  
FIG. 144  
FIG. 145  
FIG. 146  
FIG. 147  
FIG. 148  
FIG. 149  
FIG. 150  
FIG. 151  
FIG. 152  
FIG. 153  
FIG. 154  
FIG. 155  
FIG. 156  
FIG. 157  
FIG. 158  
FIG. 159  
FIG. 160  
FIG. 161  
FIG. 162  
FIG. 163  
FIG. 164  
FIG. 165  
FIG. 166  
FIG. 167  
FIG. 168  
FIG. 169  
FIG. 170  
FIG. 171  
FIG. 172  
FIG. 173  
FIG. 174  
FIG. 175  
FIG. 176  
FIG. 177  
FIG. 178  
FIG. 179  
FIG. 180  
FIG. 181  
FIG. 182  
FIG. 183  
FIG. 184  
FIG. 185  
FIG. 186  
FIG. 187  
FIG. 188  
FIG. 189  
FIG. 190  
FIG. 191  
FIG. 192  
FIG. 193  
FIG. 194  
FIG. 195  
FIG. 196  
FIG. 197  
FIG. 198  
FIG. 199  
FIG. 200  
FIG. 201  
FIG. 202  
FIG. 203  
FIG. 204  
FIG. 205  
FIG. 206  
FIG. 207  
FIG. 208  
FIG. 209  
FIG. 210  
FIG. 211  
FIG. 212  
FIG. 213  
FIG. 214  
FIG. 215  
FIG. 216  
FIG. 217  
FIG. 218  
FIG. 219  
FIG. 220  
FIG. 221  
FIG. 222  
FIG. 223  
FIG. 224  
FIG. 225  
FIG. 226  
FIG. 227  
FIG. 228  
FIG. 229  
FIG. 230  
FIG. 231  
FIG. 232  
FIG. 233  
FIG. 234  
FIG. 235  
FIG. 236  
FIG. 237  
FIG. 238  
FIG. 239  
FIG. 240  
FIG. 241  
FIG. 242  
FIG. 243  
FIG. 244  
FIG. 245  
FIG. 246  
FIG. 247  
FIG. 248  
FIG. 249  
FIG. 250  
FIG. 251  
FIG. 252  
FIG. 253  
FIG. 254  
FIG. 255  
FIG. 256  
FIG. 257  
FIG. 258  
FIG. 259  
FIG. 260  
FIG. 261  
FIG. 262  
FIG. 263  
FIG. 264  
FIG. 265  
FIG. 266  
FIG. 267  
FIG. 268  
FIG. 269  
FIG. 270  
FIG. 271  
FIG. 272  
FIG. 273  
FIG. 274  
FIG. 275  
FIG. 276  
FIG. 277  
FIG. 278  
FIG. 279  
FIG. 280  
FIG. 281  
FIG. 282  
FIG. 283  
FIG. 284  
FIG. 285  
FIG. 286  
FIG. 287  
FIG. 288  
FIG. 289  
FIG. 290  
FIG. 291  
FIG. 292  
FIG. 293  
FIG. 294  
FIG. 295  
FIG. 296  
FIG. 297  
FIG. 298  
FIG. 299  
FIG. 300  
FIG. 301  
FIG. 302  
FIG. 303  
FIG. 304  
FIG. 305  
FIG. 306  
FIG. 307  
FIG. 308  
FIG. 309  
FIG. 310  
FIG. 311  
FIG. 312  
FIG. 313  
FIG. 314  
FIG. 315  
FIG. 316  
FIG. 317  
FIG. 318  
FIG. 319  
FIG. 320  
FIG. 321  
FIG. 322  
FIG. 323  
FIG. 324  
FIG. 325  
FIG. 326  
FIG. 327  
FIG. 328  
FIG. 329  
FIG. 330  
FIG. 331  
FIG. 332  
FIG. 333  
FIG. 334  
FIG. 335  
FIG. 336  
FIG. 337  
FIG. 338  
FIG. 339  
FIG. 340  
FIG. 341  
FIG. 342  
FIG. 343  
FIG. 344  
FIG. 345  
FIG. 346  
FIG. 347  
FIG. 348  
FIG. 349  
FIG. 350  
FIG. 351  
FIG. 352  
FIG. 353  
FIG. 354  
FIG. 355  
FIG. 356  
FIG. 357  
FIG. 358  
FIG. 359  
FIG. 360  
FIG. 361  
FIG. 362  
FIG. 363  
FIG. 364  
FIG. 365  
FIG. 366  
FIG. 367  
FIG. 368  
FIG. 369  
FIG. 370  
FIG. 371  
FIG. 372  
FIG. 373  
FIG. 374  
FIG. 375  
FIG. 376  
FIG. 377  
FIG. 378  
FIG. 379  
FIG. 380  
FIG. 381  
FIG. 382  
FIG. 383  
FIG. 384  
FIG. 385  
FIG. 386  
FIG. 387  
FIG. 388  
FIG. 389  
FIG. 390  
FIG. 391  
FIG. 392  
FIG. 393  
FIG. 394  
FIG. 395  
FIG. 396  
FIG. 397  
FIG. 398  
FIG. 399  
FIG. 400  
FIG. 401  
FIG. 402  
FIG. 403  
FIG. 404  
FIG. 405  
FIG. 406  
FIG. 407  
FIG. 408  
FIG. 409  
FIG. 410  
FIG. 411  
FIG. 412  
FIG. 413  
FIG. 414  
FIG. 415  
FIG. 416  
FIG. 417  
FIG. 418  
FIG. 419  
FIG. 420  
FIG. 421  
FIG. 422  
FIG. 423  
FIG. 424  
FIG. 425  
FIG. 426  
FIG. 427  
FIG. 428  
FIG. 429  
FIG. 430  
FIG. 431  
FIG. 432  
FIG. 433  
FIG. 434  
FIG. 435  
FIG. 436  
FIG. 437  
FIG. 438  
FIG. 439  
FIG. 440  
FIG. 441  
FIG. 442  
FIG. 443  
FIG. 444  
FIG. 445  
FIG. 446  
FIG. 447  
FIG. 448  
FIG. 449  
FIG. 450  
FIG. 451  
FIG. 452  
FIG. 453  
FIG. 454  
FIG. 455  
FIG. 456  
FIG. 457  
FIG. 458  
FIG. 459  
FIG. 460  
FIG. 461  
FIG. 462  
FIG. 463  
FIG. 464  
FIG. 465  
FIG. 466  
FIG. 467  
FIG. 468  
FIG. 469  
FIG. 470  
FIG. 471  
FIG. 472  
FIG. 473  
FIG. 474  
FIG. 475  
FIG. 476  
FIG. 477  
FIG. 478  
FIG. 479  
FIG. 480  
FIG. 481  
FIG. 482  
FIG. 483  
FIG. 484  
FIG. 485  
FIG. 486  
FIG. 487  
FIG. 488  
FIG. 489  
FIG. 490  
FIG. 491  
FIG. 492  
FIG. 493  
FIG. 494  
FIG. 495  
FIG. 496  
FIG. 497  
FIG. 498  
FIG. 499  
FIG. 500  
FIG. 501  
FIG. 502  
FIG. 503  
FIG. 504  
FIG. 505  
FIG. 506  
FIG. 507  
FIG. 508  
FIG. 509  
FIG. 510  
FIG. 511  
FIG. 512  
FIG. 513  
FIG. 514  
FIG. 515  
FIG. 516  
FIG. 517  
FIG. 518  
FIG. 519  
FIG. 520  
FIG. 521  
FIG. 522  
FIG. 523  
FIG. 524  
FIG. 525  
FIG. 526  
FIG. 527  
FIG. 528  
FIG. 529  
FIG. 530  
FIG. 531  
FIG. 532  
FIG. 533  
FIG. 534  
FIG. 535  
FIG. 536  
FIG. 537  
FIG. 538  
FIG. 539  
FIG. 540  
FIG. 541  
FIG. 542  
FIG. 543  
FIG. 544  
FIG. 545  
FIG. 546  
FIG. 547  
FIG. 548  
FIG. 549  
FIG. 550  
FIG. 551  
FIG. 552  
FIG. 553  
FIG. 554  
FIG. 555  
FIG. 556  
FIG. 557  
FIG. 558  
FIG. 559  
FIG. 560  
FIG. 561  
FIG. 562  
FIG. 563  
FIG. 564  
FIG. 565  
FIG. 566  
FIG. 567  
FIG. 568  
FIG. 569  
FIG. 570  
FIG. 571  
FIG. 572  
FIG. 573  
FIG. 574  
FIG. 575  
FIG. 576  
FIG. 577  
FIG. 578  
FIG. 579  
FIG. 580  
FIG. 581  
FIG. 582  
FIG. 583  
FIG. 584  
FIG. 585  
FIG. 586  
FIG. 587  
FIG. 588  
FIG. 589  
FIG. 590  
FIG. 591  
FIG. 592  
FIG. 593  
FIG. 594  
FIG. 595  
FIG. 596  
FIG. 597  
FIG. 598  
FIG. 599  
FIG. 600  
FIG. 601  
FIG. 602  
FIG. 603  
FIG. 604  
FIG. 605  
FIG. 606  
FIG. 607  
FIG. 608  
FIG. 609  
FIG. 610  
FIG. 611  
FIG. 612  
FIG. 613  
FIG. 614  
FIG. 615  
FIG. 616  
FIG. 617  
FIG. 618  
FIG. 619  
FIG. 620  
FIG. 621  
FIG. 622  
FIG. 623  
FIG. 624  
FIG. 625  
FIG. 626  
FIG. 627  
FIG. 628  
FIG. 629  
FIG. 630  
FIG. 631  
FIG. 632  
FIG. 633  
FIG. 634  
FIG. 635  
FIG. 636  
FIG. 637  
FIG. 638  
FIG. 639  
FIG. 640  
FIG. 641  
FIG. 642  
FIG. 643  
FIG. 644  
FIG. 645  
FIG. 646  
FIG. 647  
FIG. 648  
FIG. 649  
FIG. 650  
FIG. 651  
FIG. 652  
FIG. 653  
FIG. 654  
FIG. 655  
FIG. 656  
FIG. 657  
FIG. 658  
FIG. 659  
FIG. 660  
FIG. 661  
FIG. 662  
FIG. 663  
FIG. 664  
FIG. 665  
FIG. 666  
FIG. 667  
FIG. 668  
FIG. 669  
FIG. 670  
FIG. 671  
FIG. 672  
FIG. 673  
FIG. 674  
FIG. 675  
FIG. 676  
FIG. 677  
FIG. 678  
FIG. 679  
FIG. 680  
FIG. 681  
FIG. 682  
FIG. 683  
FIG. 684  
FIG. 685  
FIG. 686  
FIG. 687  
FIG. 688  
FIG. 689  
FIG. 690  
FIG. 691  
FIG. 692  
FIG. 693  
FIG. 694  
FIG. 695  
FIG. 696  
FIG. 697  
FIG. 698  
FIG. 699  
FIG. 700  
FIG. 701  
FIG. 702  
FIG. 703  
FIG. 704  
FIG. 705  
FIG. 706  
FIG. 707  
FIG. 708  
FIG. 709  
FIG. 710  
FIG. 711  
FIG. 712  
FIG. 713  
FIG. 714  
FIG. 715  
FIG. 716  
FIG. 717  
FIG. 718  
FIG. 719  
FIG. 720  
FIG. 721  
FIG. 722  
FIG. 723  
FIG. 724  
FIG. 725  
FIG. 726  
FIG. 727  
FIG. 728  
FIG. 729  
FIG. 730  
FIG. 731  
FIG. 732  
FIG. 733  
FIG. 734  
FIG. 735  
FIG. 736  
FIG. 737  
FIG. 738  
FIG. 739  
FIG. 740  
FIG. 741  
FIG. 742  
FIG. 743  
FIG. 744  
FIG. 745  
FIG. 746  
FIG. 747  
FIG. 748  
FIG. 749  
FIG. 750  
FIG. 751  
FIG. 752  
FIG. 753  
FIG. 754  
FIG. 755  
FIG. 756  
FIG. 757  
FIG. 758  
FIG. 759  
FIG. 760  
FIG. 761  
FIG. 762  
FIG. 763  
FIG. 764  
FIG. 765  
FIG. 766  
FIG. 767  
FIG. 768  
FIG. 769  
FIG. 770  
FIG. 771  
FIG. 772  
FIG. 773  
FIG. 774  
FIG. 775  
FIG. 776  
FIG. 777  
FIG. 778  
FIG. 779  
FIG. 780  
FIG. 781  
FIG. 782  
FIG. 783  
FIG. 784  
FIG. 785  
FIG. 786  
FIG. 787  
FIG. 788  
FIG. 789  
FIG. 790  
FIG. 791  
FIG. 792  
FIG. 793  
FIG. 794  
FIG. 795  
FIG. 796  
FIG. 797  
FIG. 798  
FIG. 799  
FIG. 800  
FIG. 801  
FIG. 802  
FIG. 803  
FIG. 804  
FIG. 805  
FIG. 806  
FIG. 807  
FIG. 808  
FIG. 809  
FIG. 810  
FIG. 811  
FIG. 812  
FIG. 813  
FIG. 814  
FIG. 815  
FIG. 816  
FIG. 817  
FIG. 818  
FIG. 819  
FIG. 820  
FIG. 821  
FIG. 822  
FIG. 823  
FIG. 824  
FIG. 825  
FIG. 826  
FIG. 827  
FIG. 828  
FIG. 829  
FIG. 830  
FIG. 831  
FIG. 832  
FIG. 833  
FIG. 834  
FIG. 835  
FIG. 836  
FIG. 837  
FIG. 838  
FIG. 839  
FIG. 840  
FIG. 841  
FIG. 842  
FIG. 843  
FIG. 844  
FIG. 845  
FIG. 846  
FIG. 847  
FIG. 848  
FIG. 849  
FIG. 850  
FIG. 851  
FIG. 852  
FIG. 853  
FIG. 854  
FIG. 855  
FIG. 856  
FIG. 857  
FIG. 858  
FIG. 859  
FIG. 860  
FIG. 861  
FIG. 862  
FIG. 863  
FIG. 864  
FIG. 865  
FIG. 866  
FIG. 867  
FIG. 868  
FIG. 869  
FIG. 870  
FIG. 871  
FIG. 872  
FIG. 873  
FIG. 874  
FIG. 875  
FIG. 876  
FIG. 877  
FIG. 878  
FIG. 879  
FIG. 880  
FIG. 881  
FIG. 882  
FIG. 883  
FIG. 884  
FIG. 885  
FIG. 886  
FIG. 887  
FIG. 888  
FIG. 889  
FIG. 890  
FIG. 891  
FIG. 892  
FIG. 893  
FIG. 894  
FIG. 895  
FIG. 896  
FIG. 897  
FIG. 898  
FIG. 899  
FIG. 900  
FIG. 901  
FIG. 902  
FIG. 903  
FIG. 904  
FIG. 905  
FIG. 906  
FIG. 907  
FIG. 908  
FIG. 909  
FIG. 910  
FIG. 911  
FIG. 912  
FIG. 913  
FIG. 914  
FIG. 915  
FIG. 916  
FIG. 917  
FIG. 918  
FIG. 919  
FIG. 920  
FIG. 921  
FIG. 922  
FIG. 923  
FIG. 924  
FIG. 925  
FIG. 926  
FIG. 927  
FIG. 928  
FIG. 929  
FIG. 930  
FIG. 931  
FIG. 932  
FIG. 933  
FIG. 934  
FIG. 935  
FIG. 936  
FIG. 937  
FIG. 938  
FIG. 939  
FIG. 940  
FIG. 941  
FIG. 942  
FIG. 943  
FIG. 944  
FIG. 945  
FIG. 946  
FIG. 947  
FIG. 948  
FIG. 949  
FIG. 950  
FIG. 951  
FIG. 952  
FIG. 953  
FIG. 954  
FIG. 955  
FIG. 956  
FIG. 957  
FIG. 958  
FIG. 959  
FIG. 960  
FIG. 961  
FIG. 962  
FIG. 963  
FIG. 964  
FIG. 965  
FIG. 966  
FIG. 967  
FIG. 968  
FIG. 969  
FIG. 970  
FIG. 971  
FIG. 972  
FIG. 973  
FIG. 974  
FIG. 975  
FIG. 976  
FIG. 977  
FIG. 978  
FIG. 979  
FIG. 980  
FIG. 981  
FIG. 982  
FIG. 983  
FIG. 984  
FIG. 985  
FIG. 986  
FIG. 987  
FIG. 988  
FIG. 989  
FIG. 990  
FIG. 991  
FIG. 992  
FIG. 993  
FIG. 994  
FIG. 995  
FIG. 996  
FIG. 997  
FIG. 998  
FIG. 999  
FIG. 1000